

Drone Signal Detection And Simulation Devices

SMA J1-1500

1.5km Long Distance Hand-gun Type Signal Simulator



Parameters

Features

- Detachable 7000mAh low-temperature resistant battery.
- Signal simulation capabilities include crash landing and return.
- Maximum 30W power per channel.
- Up to 8 channels for increased flexibility.
- Equipped with aiming sight and portable backpack.
- Includes car charger for added convenience.
- Customizable frequency bands and channels per demand.

Packaging

Package Dimensions	918*339*130 mm
Package Weight	6 kg

Signal Simulation

Signal Simulation Distance	1200 m
Antenna Gain	≥10 dBi
Signal Simulation Response Time	1s
Signal Simulation Angle	60°

General

Power Source	LiPo
Total Power	350 W
Continuous Operation Time	45 min
Dimensions	850*278.5*82.8 mm
Weight	4 kg

Environment

IP Protection Rating	IP54
Operating Temperature	-20 ~ 60°C

6-ch

6-ch Type A Standard 6-ch	430~440 MHz 860~930 MHz	1555~1620 MHz 2400~2500 MHz	5100~5350 MHz 5700~5840 MHz
6-ch Type B Dual-channel 2.4 GHz	860~930 MHz 1555~1620 MHz	2400~2500 MHz 5700~5840 MHz	5100~5350 MHz 5700~5840 MHz
6-ch Type C Dual-channel 2.4 GHz and 5.8 GHz	1555~1620 MHz 2400~2500 MHz	2400~2500 MHz 5100~5350 MHz	5700~5840 MHz 5700~5840 MHz

8-ch

8-ch Type A Standard 8-ch	430~440 MHz 860~930 MHz	1150~1380 MHz 1380~1450 MHz	1555~1620 MHz 2400~2500 MHz	5100~5350 MHz 5700~5840 MHz
8-ch Type B Dual-channel 2.4 GHz	430~440 MHz 860~930 MHz	1555~1620 MHz 2400~2500 MHz	2400~2500 MHz 5100~5350 MHz	5700~5840 MHz 5840~5940 MHz
8-ch Type C Dual-channel 2.4 GHz and 5.8 GHz	860~930 MHz 1555~1620 MHz	2400~2500 MHz 2400~2500 MHz	5100~5350 MHz 5700~5840 MHz	5700~5840 MHz 5840~5940 MHz

CONTACT CHINA MONEYPRO GROUP NOW:

EMAIL: SALES@MONEYPROUAV.COM

MOBILE: +86-18126437260 (WHAT'S UP) MS. AMY LUO