

Gimbal Camera



MG360R



MG360RL

Features	• Equipped with visible light imaging capability.	• Visible and infrared dual-mode imaging capability.
	• Ground target detection and recognition ability.	• Ground target detection and recognition ability.
	• Automatic capture functionality.	• Search, track, lock, and guide working modes.
	• Photo and video recording features.	• Target location and positioning functionality.
	• Target GPS information logging capability.	• Laser illumination and rangefinding features.
Gimbal		
Stabilized System	2-axis	2-axis
Mechanical Range	360° continuous Pan; Pitch: -110~ +10°	360° continuous Pan; Pitch: -110~ +10°
Zoom Camera		
Sensor	1/2.8" CMOS	1/2.8" CMOS
Effective Pixels	213 MP	213 MP
Resolution	1920*1080	1920*1080
Focal length	4.3-129 mm	4.3-129 mm
Optical Zoom	30x	30x
Digital Zoom	12x	12x
Max. Zoom	360x	360x
Thermal Camera		
Focal length	35 mm	35 mm
Resolution	640*512	640*512
Digital Zoom	2x / 4x	2x / 4x
Pixel Pitch	12 μm	12 μm
Spectral Band	8-14 μm	8-14 μm
Laser Range Finder		
Wave length	1535 nm	1064 nm
Measurement accuracy	± 1 m	± 1 m
Measurement range	50-3000 m	120-5000 m
General		
Dimensions	135*135*180mm	172*172*200 mm
Weight	1.2 kg	2.5 kg
Voltage	12 V	24 V
Operating Temperature	-20~60 °C	-20~60 °C
Laser Illuminator		
Illumination Range		≥ 2 km
Continuous Time		≥ 20 s
Encoding Accuracy		≤ 2.5 μs

CONTACT CHINA MONEYPRO GROUP NOW:

EMAIL: SALES@MONEYPROUAV.COM

MOBILE: +86-18126437260 (WHAT'S UP) MS. AMY LUO