MAD80

80km Data Link with Tracking Antenna

80km long distance data link, featuring high integration, stable performance, and high reliability.

MMD80

80km Data Link with Anti-Interference Module

80km long-distance data link, capable of controlling wireless silence, multi-link radio communication, and timed radio communication. Integrated with various anti-interference methods.



Parameters

on ground unit.

Dual-axis auto-tracking gimbal: Accurately tracks drone's direction and position in real-time. High-gain directional antenna: Enhances wireless signal reception.

- ·Advanced RF technology: Offers strong anti-interference and automatic encryption.
- ·Modular, high-integration design: Ensures convenient, efficient usage

Video

 View Quality
 1080p / 60fps

 Codec
 H.265 / H.264

 Video Bit Rate
 500 KB/s−5 MB/s

 Video Latency
 ≤ 200ms

Video Latency ≤ 200ms

Data Latency ≤ 30ms

Interface

Antenna Airborne Unit: 2*SMA / Ground Unit: N-type female Power Airborne Unit: 1*T30 / Ground-based Unit: 1*T60

Serial Airborne Unit: 1*RS232, 1*TTL Ground Unit: 2*RS232

2*SBUS

SBUS

Ethernet Airborne Unit: 1*4Pin / Ground Unit: 1*RJ45

Environment

IP Protection Rating IP54
Operating Temperature -40~ 70°C

General

Dimensions Airborne Unit: 100*63*22 mm

Ground Unit: 450*390*175 mm

Weight Airborne Unit: 140.8 g Ground Unit: 5000 g

Wireless

Channel Bandwidth 5 MHz . 10 MHz . 20 MHz

 Modulation Mode
 OFDM

 Transmission Power
 33 dBm

 Sensitivity
 ≤ -89dBm

 Max. Transmission Distance
 80 km

 Max. Download Speed
 30 MB/s

Airborne Antenna

Antenna Interface SMA

Polarization Type Vertical polarization

Antenna Gain 2.5dBi
Antenna Standing Wave Ratio ≤2.0

Ground Antenna

Antenna Interface N-type female
Polarization Type Vertical polarization

Antenna Gain 16dBi+4dBi
Antenna Standing Wave Ratio ≤ 2.0
Pitch Angle 360°
Horizontal Angle -15~135°
Max. Speed 60°/s

Power

Airborne Unit ≤ 7W
Ground Unit ≤ 30W

CONTACT CHINA MONEYPRO GROUP NOW:

EMAIL: SALES@MONEYPROUAV. COM

MOBILE: +86-18126437260 (WHAT'S UP) MS. AMY LUO