
Functional Features

- Quick Focus
- ➤ 170ms Low Latency RTSP Video Format
- ➤ High-precision FOC
- > Integrated Ground Station Software


Device Structure



Annotation① : 45X hybrid zoom: 5X optical zoom * 9X digital zoom



Voltage		DC 12V-26.2V ^③	
Power Supply		Static 5W	
Characterist ics	Roll Angle Range	-45~+45°	
	Pitch Angle Range	-40~+100°	
	Course Angle Range	-145° ∼+145°	
	Pitch and Roll Angle Jitter	$\pm0.02^\circ$	
	Horizontal Angle Jitter	±0.03°	
	One-click Return Function	Quick return to initial position with one click	
	Adjustable PTZ Speed	The current speed mode based on the multiple zoom of camera	
	Control Modes	IP and UART and S.BUS control (or PWM for Option)	
Visible Light Camera	CMOS Size	1/3" CMOS SENSOR: 4 Mega Pixels	
	Optical zoom	5x HD optical zoom lens, $f=5\pm10\%\sim25\pm10\%$ mm	
	Focusing Time	Real time fast focusing, focusing time <1S	
	Video Format	RTSP 1080P and Local TF 1080P record	
	Field Angle (FOV)	D : WIDE 61.1° TELE 12.41°	
		H : WIDE 50.12° TELE 10.81°	
		V : WIDE 38.07° TELE 8.13°	
	Support Mode	1080P 30fps	
LRF	Laser wave	905nm (class 1 laser)	
	Detect range	$5{\sim}1200$ m	
	Accuracy / Resolution	±1 m	
Size		120mm $ imes$ 113 mm	
Operating Temperature		-10℃ to +45℃ / 20% to 80% RH	
Storage Temperature		-20°C to +60°C / 20% to 95% RH	
Application		UAV aerial photography	
Weight		240±10	



Item	Model	Interfaces	Definition	Function
1		Signal	Tx+	IP
2		Signal	Tx-	IP
3		Signal	Rx+	IP
4		Signal	Rx-	IP
5	10 PIN	Signal	S. BUS	S. BUS Input
6	Socket	Signal GND	GND	GND
7		Signal	RX	UART Reception
8		Signal	TX	UART Transmission
9		Power GND	GND	GND
10		Power Output	VCC	DC 12V-26.2V

^{*}Due to product upgrade, appearance/size/weight/power consumption may change slightly. Please contact sales for the latest data.

CONTACT CHINA MONEYPRO GROUP NOW:

EMAIL: SALES@MONEYPROUAV. COM

MOBILE: +86-18126437260 (WHAT'S UP) MS. AMY LUO