


Functional Features

- 140X Hybrid Zoom^①
- AI Target Tracking
- Four Supplement Lights
- 3-Axis Stability
- IP and UART Control
- TF Card Storage

Device Structure




		
Voltage		DC12V-26.2V
Power Supply		Dynamic 10W
PTZ	Roll Angle Range	-45°~ +45°
	Pitch Angle Range	-45°~ +120°
	Yaw Angle Range	-280°~ +280°
	Pitch and Roll Angle Jitter	±0.02°
	Horizontal Angle Jitter	±0.03°
	One-click Return Function	Quick return to initial position with one click
	Adjustable PTZ Speed	The current speed mode based on the multiple zoom of camera
	Control Modes	IP and UART and S.BUS control (or PWM for Option)
Visible Camera	CMOS Size	1/1.8" WDR CMOS SENSOR: 8 Mega Pixels
	Optical Zoom	20X optical zoom HD lens, f=6.7±5%~125±5%mm
	Focusing time	Real-time fast focusing function, focusing time <1S
	Video Output	IP Output 1080P, Local TF Card Storage
	FOV	D : WIDE 66.6°±5% TELE 4.0°±5% H : WIDE 59.6°±5% TELE 3.5°±5% V : WIDE 35.7°±5% TELE 2.0°±5%
	Video Output	1080P 30fps
Embedded AI Function	Min. tracking target size	16×16 Pixels
	Max. tracking target size	256×256 Pixels
	Target Memory Time	2 seconds
	Tracking speed	50 pixel/frame max
	Simultaneous detection qty	100 targets max
	Targets type	Human and Vehicles
HDMI Video Output		1080P 60fps
Size		103.7mm×170.95mm×168.24mm
Operating Temperature		-10°C to +55°C / 20% to 80% RH
Storage Temperature		-20°C to +60°C / 20% to 95% RH

Weight	803±20 grams
--------	--------------

Connection Diagram

Electricity Interfaces



No.	Model	Type	Interface Definition	Function
1	6PIN Socket	Communication Interface	485+	485 Interface
2		Communication Interface	485-	485 Interface
3		Communication Interface	Rx-	IP
4		Communication Interface	Rx+	IP
5		Communication Interface	Tx-	IP
6		Communication Interface	Tx+	IP

No.	Model	Type	Interface Definition	Function
1	8PIN Socket	Communication Interface	GND	GND
2		Communication Interface	SBUS	SBUS Input
3		Communication Interface	TXD3	UART Transmission
4		Communication Interface	RXD3	UART Reception
5		Communication Interface	Rx-	IP
6		Communication Interface	Rx+	IP
7		Communication Interface	Tx-	IP

CONTACT CHINA MONEYPRO GROUP NOW:

EMAIL: SALES@MONEYPROUAV.COM

MOBILE: +86-18126437260 (WHAT'S UP) MS. AMY LUO