





Surge Arrester

	Type	N-KKYP
	Cycle number range	DC~2500MHz
	VSWR	Less than 1.1
	Loss	Less than 0.2dB
	Withstand Power	200W PEP
	Discharge Ionization Voltage	DC230V ± 15%
	Shock discharge voltage	1000V
	Shock current tolerance	6000A
	Shock wave repeated discharge tolerance	More than 500 times
	Insulation resistance DC-100V	More than 10000MΩ
	Connector	NJ/NJ
	Size	78W X 41H X 20Dmm
	Weight	113g
	Type	N-KKYP
	Cycle number range	DC~2500MHz
	VSWR	Less than 1.1
	Loss	Less than 0.2dB
	Withstand Power	400W PEP
	Discharge Ionization Voltage	DC350V ± 15%
	Shock discharge voltage	1000V
	Shock current tolerance	6000A
	Shock wave repeated discharge tolerance	More than 500 times
	Insulation resistance DC-100V	More than 10000MΩ
	Connector	NJ/NJ
	Size	77W X 41H X 20Dmm
	Weight	114g

CONTACT CHINA MONEYPRO GROUP NOW:

EMAIL: SALES@MONEYPROUAV.COM

MOBILE: +86-18126437260 (WHAT'S UP) MS. AMY LUO