

Tethered Device

Parameters

Features

- Maximum power 5 kw, Moneypro 4 supports loads up to 10 kg
- Cable length 120 m (without fiber optics), automatic payoff and take-up.
- Over-voltage, over-current, over-temperature, short-circuit protection and so on.
- Compatible with standard smart battery slots.
- Small size and light weight.

Airborne Side

Dimensions	282*143*98 mm
Weights	2 kg
Input Voltage	DC 400V
Output Voltage	DC 50V
Max. Power	5 kw
Protective Function	Output short-circuit and over-temperature protection
Operating Temperature	-20~50°C

Ground Side

Dimensions	450*300*460 mm
Total Weight	20 kg (Tethered Ground Integration Unit)
Input Voltage	AC220V / 380V
Output Voltage	DC 400V
Max. Power	Rated power: 7 KW / Max. instantaneous power: ≤8100 W
Protective Function	Output short-circuit and over-temperature protection
Operating Temperature	-20~50°C
Wire Outer Diameter	Approx. Φ4.5 mm
Operating Mode	Active Unwind / Active Take-Up
Voltage Compensation	Support
Conductor Resistance	1.1 Ω@100 m, single positive pole
Working Altitude	< 5000 m
Protective Function	Over-voltage, over-current, output short-circuit, over-temperature protection



(Airborne Side)

(Ground Side)

CONTACT CHINA MONEYPRO GROUP NOW:

EMAIL: SALES@MONEYPROUAV.COM

MOBILE: +86-18126437260 (WHAT'S UP) MS. AMY LUO